

**Oenolab Diagnostics**

49 rue de l'industrie  
ZI les Joncaux  
64700 Hendaye  
France

Phone: +33 (0)5 59 63 89 54

Email : labo@oenolab.com

Web: www.oenolab.com



## OENOFLOW +

**Oenolab diagnostics is proud to introduce OenoFlow +**



**OenoFlow + is a versatile and powerful semi-automatic analyzer with:**

- User-friendly interface with 7" TFT touch screen
- External keyboard and mouse support via USB
- Up to 200 tests can be programmed
- Testing modes: Flowcell or cuvette
- Analysis method: Absorbance, Endpoint, Fixed-time, Kinetics ...
- Wavelengths range from 340 to 670 nm
- Universal power supply
- Power-failure protection



It is sophisticated but user friendly on board software with large LCD touch-screen.

- Simple parameters setup.
- Quick interchange between 4 temperature options.
- Support Bi-chromatic tests.
- Multi-functional and comprehensive testing panel interface.
- Real-time monitoring of reaction curve and temperature change.
- Parameters can be reviewed in test panel

Support two testing modes:  
Flowcell or cuvette  
Easy to shift between modes

Easy maintenance:  
Remove back cover to change lamp



Technical Specification	
Measurement range	0.000 to 3.500 Absorbance units (A)
Stability	< 0.005 A / 20 min @ 340 nm
Wavelengths	8 position filter wheel with 340, 405, 450, 510, 546, 578, 630 and 670 nm
Flowcell	Stainless steel with quartz window with 32 $\mu$ l volume and optical path: 10 mm Aspiration volume: 200 to 9000 $\mu$ l
Light source	Tungsten-halogen 6V & 10W
Display	7" Touch screen with touch pen and popup keypad
Printer	Built-in thermal printer
Memory	200 tests / 3000 results
Analysis mode	Absorbance / Fixed time / End point / Kinetic ...
Interface	RS232 serial port supporting data transmission
Operating conditions	100 to 240 V, 50/60 Hz
Dimension / Weight	L x W x H = 43 x 36 x 17 cm / 6.8 kg